



**NOTES:**

1. MIN. 3000 mm WIDE CONCRETE ISLAND, IN SPECIAL CIRCUMSTANCES, ABSOLUTE MIN. WIDTH CAN BE 2000 mm
2. SUPPLY AND INSTALL 150mm GRANULAR 'A' BASE.
4. ALL TACTILE WALKING SURFACE INDICATOR DETECTABLE WARNING PLATE DESIGNS ARE TO BE FINALIZED BY THE PLATE MANUFACTURER (610 mm x 610 mm SQUARE OR RADIAL EDGE OF PLATES TO MATCH CURB RADIUS.)
5. TACTILE WALKING SURFACE INDICATOR PLATES TO BE PLACED 150 mm OFFSET FROM BACK OF CURB (200 mm MAXIMUM). MINIMUM 150 mm CONCRETE REQUIRED FROM OUTER EDGE OF PLATE ASSEMBLY TO EDGE OF SIDEWALK.
6. CONSTRUCT PEDESTRIAN REFUGE ISLAND, WITH CURB FACE AS SEMI-MOUNTABLE CURB AS PER OPSD 600.090 WITH 32MPa CONCRETE. DROP CURBS TO BE CONSTRUCTED TO CREATE A FLUSH TRANSITION WITH THE ASPHALT AS INDICATED IN CROSS SECTION C-C'.
7. IN RETROFIT SITUATIONS, SAWCUT EXISTING ASPHALT AND POUR CONCRETE AGAINST SAWCUT EDGE.

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SHOWN.

**STANDARD DRAWING**

REV 1      MAY 2023

**PEDESTRIAN REFUGE ISLAND**



**CW-241**