

1.5m HIGH BLACK VINYL CHAINLINK FENCE INSTALLED 150mm FROM PROPERTY LINE. REFER TO C.O.W. STANDARD DRAWING CW-805.

REFER TO DESIGN DRAWINGS FOR PROPOSED WIDTH AND SURFACE TREATMENT.

VARIES

150

150

TAMP EDGE AT 45 DEGREE ANGLE (BASE AND SURFACE ASPHALT)

40 mm COMPACTED DEPTH OF HL-3 ASPHALT

60 mm COMPACTED DEPTH OF HL-8 ASPHALT

1500

2%

150 mm GRANULAR 'A', COMPACTED TO 100% S.P.M.D.D.

300 mm GRANULAR 'B' COMPACTED TO 100% S.P.D. (ADDITIONAL DEPTHS IF REQUIRED PER GEOTECHNICAL RECOMMENDATIONS)

NON-WOVEN SYNTHETIC GEO-TEXTILE FABRIC INSTALLED ON COMPACTED SUB-GRADE (IF REQUIRED PER GEOTECHNICAL RECOMMENDATIONS)

COMPACTED SUBGRADE TO 95% S.P.D.

NOTES:

1. TYPICAL WALKWAY BLOCK IS 3000
2. TYPICAL EMERGENCY ACCESS BLOCK IS 6000
3. GEOTECHNICAL RECOMMENDATION IS REQUIRED. PROVIDE ADDITIONAL GRANULAR MATERIAL, TESTING, AND REPORTING RECOMMENDATIONS. RECOMMENDATION FOR ASPHALT MIX DESIGN TO BE APPROVED BY CITY.
4. ENSURE POSITIVE DRAINAGE ON WALKWAY / ACCESS. SURFACE WATER MUST NOT BE COLLECTED AND CONVEYED ALONG WALKWAY / ACCESS SURFACE.
5. EMERGENCY ACCESS BLOCKS REQUIRE BOLLARD GATES, REFER TO C.O.W. DOUBLE 1.8M BOLLARD GATE DETAIL, STANDARD DRAWING CW-522.
6. REFER TO OPSS 1150 AND OPSS 501.
7. THE CROSS SECTION MAY BE REVISED TO HAVE A CROWNED CENTRELINE AS REQUIRED FOR SITE SPECIFIC CONDITIONS.

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SHOWN.

STANDARD DRAWING

REV 1

MAY 2023

WALKWAY AND ACCESS BLOCK DETAIL



CW-502